digital™ MATERIAL SAFETY DATA SHEET

SECTION 1 - PREPARATION/PRODUCT INFORMATION

Manufacturer's Name: Digital Equipment Corporation Maynard, MA USA

Non-Emergency Phone Number: (508) 496-9242

Emergency Phone Numbers: 800-228-5635 ext.123
[+1] 612-221-3999 ext.123

Preparation Date: April 21, 1992

Supersedes: July 11, 1991

Product Name: Photoreceptor Drum
Use: Image Transfer Device

Part Number(s): LN08X-AB

SECTION 2 - INGREDIENTS

HAZARDOUS INGREDIENTS	CAS	%	ACGIH TLV	OSHA PEL	CARCINOGEN LIST IARC	CARCINOGEN LIST NTP	CARCINOGEN LIST OSHA	SARA 313
None								

Drum is classified as an article. Drum coating contains polymer binders and photoconductive compounds. See section 8 for Safe Handling/Preventive Measures.

All ingredients contained in this product are on the US TSCA inventory.

SECTION 3 - PHYSICAL AND CHEMICAL DATA

Boiling Point - Not applicable
Vapor Pressure - Not applicable
Vapor Density - Not applicable
Appearance - Solid
Freezing Point - Not applicable
Melting/Softening Point - Not applicable
Solubility in Water - Insoluble
Percent Volatile - None
Evaporation Rate - Not applicable
Odor and Odor Threshold - None
pH - Not applicable
Specific Gravity - Not applicable

SECTION 4 - FIRE AND EXPLOSION HAZARD

Flash Point - None
Auto-Ignition Temperature - Not applicable
Unusual Fire or Explosion Hazards - None
Hazardous Combustion Products - Carbon monoxide, carbon dioxide
Flammable Limits - None
Extinguishing Media - Water, foam, carbon dioxide
Special Fire Fighting Procedure - Treat as an electrical fire

© Digital Equipment Corporation. 1992. All rights reserved.

SECTION 5 - REACTIVITY DATA

Stability - Stable
Conditions to Avoid - Not available
Hazardous Decomposition Products - Not available
Hazardous Polymerization -None
Incompatibility - Strong bases/acids organic solvents

SECTION 6 - HEALTH HAZARD DATA/TOXICOLOGICAL PROPERTIES

Hazard to Humans- None during normal use. Exposure to the drum coating could occur if the drum coating were cracked or scratched. Inhalation of dust from coating may cause irritation of nose, throat, and lungs. Non-irritating, non-sensitizing.
Animal Experiment- (based on testing drum coating)
Acute- Oral LD50- >5 g/kg (practically non-toxic);
Dermal LD50- >2 g/kg (practically non-toxic);
Inhalation LC50- N/A. Non-irritating to skin and eyes. Not a skin sensitizer. Not mutagenic in Ames test.
Additional Information- section 8 for Safe Handling/Preventive Measures.

SECTION 7 - EMERGENCY/FIRST AID PROCEDURE

(Applies to the drum coating)

If Inhaled - Remove to fresh air. Support breathing if necessary and contact a physician.
If on Skin - Promptly wash skin with soap and water.
If in Eyes - Flush eyes with large quantities of water for at least 15 minutes.
If Swallowed- Seek immediate medical attention.

SECTION 8 - SAFE HANDLING/PREVENTIVE MEASURES

Personal Protective Equipment - None for normal use of drum.
Engineer Control - Not needed.
Waste Disposal - No special Requirements.
Procedures for Leaks or Spills- Not applicable
Work Practices - None
Storage Requirement- Avoid high temperature.
Handling Procedure/Equipment- Handle drum carefully to avoid damaging coating.
Labelling- None
WHMIS Classification- Not applicable

SECTION 9 - TRANSPORTATION REQUIREMENTS

None